

Product	Junction boxes
Applicant	Schneider Electric Espana S.A.U CIF: ESA08008450, C/ Bac de Roda, 52 Edificio A Planta 7, 08019 Barcelona Spain
Manufacturer	Schneider Electric Espana S.A.U CIF: ESA08008450, C/ Bac de Roda, 52 Edificio A Planta 7, 08019 Barcelona Spain
Factory	AS M ja P Nurst Ümarmäe tn 3 Kärdda 92414 Hiiumaa Estonia
Ratings	440V AC
Trade mark	ELKO
Model / Type Ref.	AS78/44 (17111 PRO-GF10)
Principal characteristics	Junction boxes for surface mounting. With floating, screw or screwless terminals. IP44. Cord anchorage type L545 or L995. L 954. For flexible cords max. 4□ or ². Cord anchorage L3044. Max. 6 stk. Vrihylser L952. L3028. Terminalblock 6 L544-4.
A sample of the product was tested and found to be in conformity with	INST EN 60670-1:2005;A1 EN 60670-22:2006
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	
Additional model(s)	(7) See page 2

Date of issue 01-09-2022

*Jiyea Gim*

Jiyea Gim  
Certification Department

**Nemko Group**

Philip Pedersens vei 11, 1366 Lysaker, Norway  
TEL +47 22 96 03 30 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

## Additional model(s)

Product	Junction boxes
Pos. No	1
Model / Type Ref.	78/44 (type 12001 L632)
Trade mark (if different from page 1)	
Rating	440V AC
Principal characteristics	Junction boxes for surface mounting. IP44/IP55. Cord anchorage type L545 or L995. L633. For flexiblecords max 4□, use cord anchorage L545 or L726. IP44. Max. 8 stk vrihylser. Max: 5x1.5mm <sup>2</sup> /klemme. Max: 4x2.5mm <sup>2</sup> /klemme. Max: 3x4.0mm <sup>2</sup> /klemme Max: 2x6.0mm <sup>2</sup> /klemme Terminalblock L544-4. L634. Max: 5x1.5mm <sup>2</sup> /klemme Max: 4x2.5mm <sup>2</sup> /klemme Max: 3x4.0mm <sup>2</sup> /klemme Max: 2x6.0mm <sup>2</sup> /klemme Surface mounted junction box with floating or screw terminals
Product	Junction boxes
Pos. No	2
Model / Type Ref.	H78/44 (6314 PRO-GF10)
Trade mark (if different from page 1)	
Rating	440V AC
Principal characteristics	Junction boxes for surface mounting. With floating, screw or screwless terminals. IP44. Cord anchorage type L545 or L995. For flexible cords max. 4□ or <sup>2</sup> . Cord anchorage L9044. Max. 6 stk. Vrihylser L952. Max: 3x4.0mm <sup>2</sup> /klemme Max: 2x6.0mm <sup>2</sup> /klemme
Product	Junction boxes
Pos. No	3
Model / Type Ref.	78/55
Trade mark (if different from page 1)	
Rating	440V AC
Principal characteristics	Junction boxes for surface mounting. IP44/IP55. Cord anchorage type L545 or L995. L212, 2.5□ or 2.5mm <sup>2</sup> . Max. 4 klemmer, max. 12 ledere, 1.5 or 1.5mm <sup>2</sup> . Max. 6 klemmer, max. 15 ledere. L214-3. IP55. Surface mounted junction box with floating terminals

Date of issue 01-09-2022



Jiyea Gim

Certification Department

**Nemko Group**

Philip Pedersens vei 11, 1366 Lysaker, Norway  
TEL +47 22 96 03 30 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Product	Junction boxes
Pos. No	4
Model / Type Ref.	78/44 (type 12001 L632)
Trade mark (if different from page 1)	
Rating	440V AC
Principal characteristics	Junction boxes for surface mounting. IP44/IP55. Cord anchorage type L545 or L995. L633. For flexiblecords max 4□, use cord anchorage L545 or L726. IP44. Max. 8 stk vrihylser. Max: 5x1.5mm <sup>2</sup> /klemme. Max: 4x2.5mm <sup>2</sup> /klemme. Max: 3x4.0mm <sup>2</sup> /klemme Max: 2x6.0mm <sup>2</sup> /klemme Surface mounted junction box with floating or screw terminals
Product	Junction boxes
Pos. No	5
Model / Type Ref.	76 (type 12001, 4, L543)
Trade mark (if different from page 1)	
Rating	440V AC
Principal characteristics	Junction boxes for surface mounting with screw terminal. Terminalblock L544-4. For flexible cords, max. 4□ or <sup>2</sup> , use cord anchorage L545. IP20. White or Black color. Max. 5 stk. Vrihylser. Max: 5x1.5mm <sup>2</sup> /klemme. Max: 4x2.5mm <sup>2</sup> /klemme. Max: 3x4.0mm <sup>2</sup> /klemme Max: 2x6.0mm <sup>2</sup> /klemme
Product	Junction boxes
Pos. No	6
Model / Type Ref.	73 (type 12001, L647)
Trade mark (if different from page 1)	
Rating	440V AC
Principal characteristics	Junction boxes for surface mounting with screw terminal. Terminalblock L544-4. IP20. Max. 3 stk. Vrihylser. Max: 5x1.5mm <sup>2</sup> /klemme. Max: 4x2.5mm <sup>2</sup> /klemme. Max: 3x4.0mm <sup>2</sup> /klemme. Max: 2x6.0mm <sup>2</sup> /klemme

Date of issue 01-09-2022

Jiyea Gim

Jiyea Gim

Certification Department

**Nemko Group**

Philip Pedersens vei 11, 1366 Lysaker, Norway

TEL +47 22 96 03 30 EMAIL info@nemko.com

ENTERPRISE NUMBER NO974404532

Product	Junction boxes
Pos. No	7
Model / Type Ref.	77 (type 12001 L3576)
Trade mark (if different from page 1)	
Rating	440V AC
Principal characteristics	Junction boxes for surface mounting with screw terminal. Equipped with knock-outs in base and means to fix wireless dimmer type LN 250 GLE/1. L3577. Terminalblock L544-4. For flexible cords max. 4mm <sup>2</sup> , use cord anchorage L545 or L995. Max: 5x1.5mm <sup>2</sup> /klemme Max: 4x2.5mm <sup>2</sup> /klemme Max: 3x4.0mm <sup>2</sup> /klemme Max: 2x6.0mm <sup>2</sup> /klemme

Date of issue 01-09-2022

*Jiyea Gim*

Jiyea Gim

Certification Department

**Nemko Group**

Philip Pedersens vei 11, 1366 Lysaker, Norway

TEL +47 22 96 03 30 EMAIL info@nemko.com

ENTERPRISE NUMBER NO974404532