

CERTIFICATE FI/41777

Our Ref. HEL-CERT191200814-04



Product Shuttered socket-outlet

Type L800 series,
L801 series
L3362 series

Trademark ELKO

Certificate Holder Elko AS
Sandstuveien 68, N-0680, Oslo City, Norway

Technical information L800 & L801 series: 16A, 250V ~
L3362 series: 16A 250/440V ~

Other information Standard sheet III
Additional information on pages 2-3

The product is certified according to the following standard(s) IEC 60884-1:2002 + A1:2006 + A2:2013
SFS 5610:2015 + A11:2016

Validity This certificate is valid until 2028-09-29 provided that the Conditions for FI certification are met. This certificate includes the right to use the FI mark under the condition that changes (if any) will be checked at SGS Fimko before the product is brought onto market and that the conditions for FI certification are met.

Date of issue 2023-09-29

SGS Fimko Ltd

Signature


Joonas Leinonen
Certification Manager



Manufacturer

Elko AS
Sandstuveien 68, N-0680, Oslo City, Norway

Manufacturing site

Merten GmbH
Fritz-Kotz-Strasse 8, 51674, Wiehl, North Rhine-Westphalia, Germany

AS M & P Nurst
Ümarmäe 3, Kärdla 92414, Hiiumaa, Estonia

Additional information

The product has certificate P23227198 issued by Nemko Group AS in accordance with the Nordic Certification Service system.

This certificate replaces previous certificate FI/41574, dated 2022-12-21, due to renewal of the certificate.

L800

Catalogue ID: RS 1091 PT
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: RS 1091 LAV PT
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: 1090 UPT IF
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic / Thermosetting, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP44 with splash screen type L478. For use in cold environment down to -25°C.

Catalogue ID: RS 1091 PT prosjektstikk
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: H 1091 PT prosjektstikk
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screwless terminals. 60mm fixing distance. IP21 with RS and Plus design

Catalogue ID: Plus dbl rehabstikk m j
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP 21 with plus design.

Additional information

Catalogue ID: RS 1091
 Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with screw terminals. 60mm fixing distance. IP21 with RS and Plus design

L801

Catalogue ID: D 1091 PT
 Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: Plus 2-vågs snabb m j
 Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with Plus design.

Catalogue ID: DR 1091 PT
 Socket-outlet for fixed installation. Alternative design. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with RS and Plus design.

L3362

Catalogue ID: RS 1091 PT DELT 440.
 Socket-outlet for fixed installation. With split output for separate phases. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: 1090 UPT IF DELT 440
 Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic / Thermosetting, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP44 with splash screen type L478. For use in cold environment down to -25°C.

As shown in the Test Report(s) No(s): REP008091