



CERTIFICATE

FOR EUROPEAN PRODUCT SAFETY

Reference No. SE-S-2300927

Socket outlets

Type designation: L801 (D 1091 PT)

Certificate holder: Elko AS
Sandstuveien 68
0680 Oslo Norway

The product complies with the standard(s): IEC 60884-1:2002+A1+A2
SS 428 08 34:2013+T1

Date of expiry: 30 August, 2028

Additional information in Appendix

Certification Body: Intertek Semko AB, Product Certification

Place: Kista - Stockholm

Signed:

Date: 30 August, 2023

Fredrik Wennersten

APPENDIX:

Reference No. SE-S-2300927

Technical Data:

<i>Type designation</i>	L801 (D 1091 PT)
<i>Rated voltage (V)</i>	250V AC
<i>Rated current (A)</i>	16 A
<i>Trademark</i>	ELKO
<i>Test Report</i>	REP008091
<i>Product information</i>	Catalogue ID: D 1091 PT. Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with RS and Plus design

Additional models

<i>Pos. No</i>	1
<i>Type designation</i>	L800 (RS 1091 PT)
<i>Rated voltage (V)</i>	250V AC
<i>Rated current (A)</i>	16 A
<i>Trademark</i>	ELKO
<i>Product information</i>	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design

<i>Pos. No</i>	2
<i>Type designation</i>	L800 (RS 1091 LAV PT)
<i>Rated voltage (V)</i>	250V AC
<i>Rated current (A)</i>	16 A
<i>Trademark</i>	ELKO
<i>Product information</i>	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design

<i>Pos. No</i>	3
<i>Type designation</i>	L800 (1090 UPT IF)
<i>Rated voltage (V)</i>	250V AC
<i>Rated current (A)</i>	16 A
<i>Trademark</i>	ELKO
<i>Product information</i>	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic / Thermosetting, flush mounting, 2 gang, with shutters and screw terminals 60mm fixing distance. IP44 with splashscreen type L478. For use in cold environment down to -25°C

<i>Pos. No</i>	4
<i>Type designation</i>	L800 (RS 1091 PT prosjektstikk)
<i>Rated voltage (V)</i>	250V AC
<i>Rated current (A)</i>	16 A
<i>Trademark</i>	ELKO
<i>Product information</i>	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design

APPENDIX:

Reference No. SE-S-2300927

<i>Pos. No</i>	5
<i>Type designation</i>	L800 (H 1091 PT projektstikk)
<i>Rated voltage (V)</i>	250V AC
<i>Rated current (A)</i>	16 A
<i>Trademark</i>	ELKO
<i>Product information</i>	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screwless terminals. 60mm fixing distance. IP21 with RS and Plus design
<i>Pos. No</i>	6
<i>Type designation</i>	L800 (Plus dbl rehabstikk m j)
<i>Rated voltage (V)</i>	250V AC
<i>Rated current (A)</i>	16 A
<i>Trademark</i>	ELKO
<i>Product information</i>	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP 20 with plus design
<i>Pos. No</i>	7
<i>Type designation</i>	L801 (Plus 2-vägs snabb m j)
<i>Rated voltage (V)</i>	250V AC
<i>Rated current (A)</i>	16 A
<i>Trademark</i>	ELKO
<i>Product information</i>	Catalogue ID: Plus 2-vägs snabb m j. Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP20 with Plus design
<i>Pos. No</i>	8
<i>Type designation</i>	L3362 (RS 1091 PT DELT 440)
<i>Rated voltage (V)</i>	250V AC
<i>Rated current (A)</i>	16 A
<i>Trademark</i>	ELKO
<i>Product information</i>	Catalogue ID: RS 1091 PT DELT 440. Socket-outlet for fixed installation. With split output for separate phases. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance.
<i>Pos. No</i>	9
<i>Type designation</i>	L801 (DR 1091 PT)
<i>Rated voltage (V)</i>	250V AC
<i>Rated current (A)</i>	16 A
<i>Trademark</i>	ELKO
<i>Product information</i>	Socket-outlet for fixed installation. Alternative design. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with RS and Plus design

APPENDIX:

Reference No. SE-S-2300927

Pos. No 10
Type designation L800 (RS 1091)
Rated voltage (V) 250V AC
Rated current (A) 16 A
Trademark ELKO
Product information Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with screw terminals. 60mm fixing distance. IP21 with RS and Plus design

Pos. No 11
Type designation L3362 (RS 1091 IF DELT 440)
Rated voltage (V) 250V AC
Rated current (A) 16 A
Trademark ELKO
Product information Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic / Thermosetting, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. For use in cold environment down to -25°C. IP44 with splashscreen type L478

Manufacturing Sites:

AS M&P Nurst
Ümarmäe 3 Kärdda
92414 Hiiumaa Estonia

Merten GmbH
Fritz-Kotz-Strasse 8
51674 Wiehl Germany

This certificate is based on a certificate with Ref. No. P23227198 dated 2023-08-11 issued by Nemko Group AS according to the Nordic Certification Service Agreement.

This certificate replaces the S certificate SE-S-2000481R2 dated 18 November 2022 due to new testing.

Certification Body: Intertek Semko AB, Product Certification **Place:** Kista - Stockholm

Signed:  **Date:** 30 August, 2023

Fredrik Wennersten