

Applicant	ELKO AS Sandstuveien 68 0680 Oslo Norway
Manufacturer	ELKO AS Sandstuveien 68 0680 Oslo Norway
Factory	See next pages
Project Number	PRJ0058109
Product	Two-pole socket-outlet without earthing contacts.
Model/Type Ref.	L800 (RS 1051 PT)
Ratings	16A 250V AC
Brandname / Trademark	ELKO
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet I. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS design
A sample of the product was tested and found to be in conformity with	Safety IEC 60884-1:2002, IEC 60884-1:2002/AMD1:2006, IEC 60884-1:2002/AMD2:2013 NEK 502:2016/AMD1:2022
Validity	<i>This certificate documents conformity with the standards shown, and also applies as license for use of Nemko's name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation.</i> <i>New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.</i>
Additional Information	
Additional model(s)	See next pages



Product	Two-pole socket-outlet without earthing contacts.
Variant	1
Model/Type Ref.	L801 (RS 1051 PT)
Ratings.	16A 250V AC
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet I. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with RS design
Product	Two-pole socket-outlet without earthing contacts.
Variant	2
Model/Type Ref.	L801 (Plus 2-vägs snabb u j)
Ratings.	16A 250V AC
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet I Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with Plus design
Product	Two-pole socket-outlet without earthing contacts.
Variant	3
Model/Type Ref.	L800 (RS 1050 PT)
Ratings.	16A 250V AC
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet I. Thermoplastic, surface mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS design
Product	Two-pole socket-outlet without earthing contacts.
Variant	4
Model/Type Ref.	L800 (Plus dbl rehabstikk u j)
Ratings.	16A 250V AC
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet I. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with plus design

Signature



Okhyun Jeon

Certification department

Date of Issue

2024-07-08

Working for a more sustainable future
Please do not print



www.nemko.com



CERTIFICATE

P24227736



Factories

Merten GmbH
Fritz-Kotz-Strasse 8
DE-51674 Wiehl
Germany

AS M ja P Nurst
Ümarmäe 3 Kärkla
Hiiumaa 92414
Estonia

Signature

Okhyun Jeon
Certification department

Date of Issue

2024-07-08

*Working for a more sustainable future
Please do not print*



www.nemko.com

Nemko Group AS
Philip Pedersens vei 11
1366 Lysaker, Norway
TEL +47 22 96 03 30
info@nemko.com
ENTERPRISE NUMBER
NO974404532