CERTIFICATE

FOR EUROPEAN PRODUCT SAFETY

Reference No. SE-S-2401349R1

Boxes for mounting in ceiling

Type designation:	L524, L524 FP, L525, L525 FP, L526, L526 FP
Certificate holder:	ELKO A/S Sandstuveien 68 0680 Oslo Norway
The product complies with the standard(s):	EN IEC 60670-1:2021 + A11 EN 60670-21:2007+A1+A11
Date of expiry:	07 October, 2030

Additional information in Appendix

Certification Body: Intertek Semko AB, Product Certification **Place:** Kista - Stockholm

Signed: **Date:** 23 April, 2026

Quan Li

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. This certificate is not issued under accreditation, by a non-approved body.

APPENDIX:

Reference No. SE-S-2401349R1

Technical Data:

Type designation	L524
Rating	70mm fixing distance
Trademark	ELKO
Test Report	REP013309
Product information	Catalogue ID 32/246: White thermoplastic box, halogen free, for ceiling mounting, with 8 conduit entries for Ø=16mm plain or corrugated conduits. 70mm fixing distance, 32mm inside depth, max. load 10kg. IP30

Type designation	L525
Pos. No.	1
Rating	70mm fixing distance
Test Report	REP013309
Product information	Catalogue ID 40/246: White thermoplastic box, halogen free, for ceiling mounting, with 8 conduit entries for Ø=16mm plain or corrugated conduits. 70mm fixing distance, 40mm inside depth, max. load 10kg. IP30

Type designation	L526
Pos. No.	2
Rating	70mm fixing distance
Test Report	REP013309
Product information	Catalogue ID 32/246: White thermoplastic box, halogen free, for ceiling mounting, with 8 conduit entries for Ø=16mm plain or corrugated conduits. 70mm fixing distance, 64mm inside depth, max. load 10kg. IP30

Type designation	L524 FP
Pos. No.	3
Rating	70mm fixing distance
Test Report	REP013309
Product information	Catalogue ID Brann 32/246: White thermoplastic box, halogen free, for ceiling mounting, with 8 conduit entries for Ø=16mm plain or corrugated conduits. 70mm fixing distance, 32mm inside depth, max. load 10kg. Provided with fire pads approved by RISE and RISEFR for fire protection through the box. IP30

Type designation	L525 FP
Pos. No.	4
Rating	70mm fixing distance
Test Report	REP013309
Product information	Catalogue ID Brann40/246: White thermoplastic box, halogen free, for ceiling mounting, with 8 conduit entries for Ø=16mm plain or corrugated conduits. 70mm fixing distance, 40mm inside depth, max. load 10kg. Provided with fire pads approved by RISE and RISEFR for fire protection through the box. IP30

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. This certificate is not issued under accreditation, by a non-approved body.

APPENDIX:

Reference No. SE-S-2401349R1

Type designation	L526 FP
Pos. No.	5
Rating	70mm fixing distance
Test Report	REP013309
Product information	Catalogue ID 64/246: White thermoplastic box, halogen free, for ceiling mounting, with 8 conduit entries for Ø=16mm plain or corrugated conduits. 70mm fixing distance, 64mm inside depth, max. load 10kg. Provided with fire pads approved by RISE and RISEFR for fire protection through the box. IP30

Manufacturing Sites: SP Moulding Poland Sp.zo.o.
Mickiewicza 6
Sieradz 98-200
POLAND

This certificate is based on a certificate with Ref. No. P24227974 dated 2024-11-26 issued by Nemko Group AS according to the Nordic Certification Service agreement.

This certificate replaces previously issued ref. No. SE-S-2401349 dated 07 October 2025. A new Certificate has been issued on account of editorial correction on the Certificate.

Certification Body: Intertek Semko AB, Product Certification **Place:** Kista - Stockholm

Signed: **Date:** 23 April, 2026

Quan Li

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. This certificate is not issued under accreditation, by a non-approved body.