

CERTIFICATE FI/40514/A1

Our Ref. HEL-CERT191200814-02



Product Shuttered socket-outlet

Type L800 series
L801 series
L3362 series

Trademark ELKO

Certificate Holder Elko AS
Sandstuveien 68, N-0680, Oslo City, Norway

Technical information 16 A, 250 V~
16 A, 440 V~ (RS 1091 PT DELT440)

Other information See principal characteristics on page 2 and 3

The product is certified according to the following standard(s) IEC 60884-1:2002 + A1:2006 + A2:2013
SFS 5610:2015 + A11:2016

Validity This certificate is valid until 2022-12-31 provided that the Conditions for FI certification are met. This certificate includes the right to use the FI mark under the condition that changes (if any) will be checked at SGS Fimko before the product is brought onto market and that the conditions for FI certification are met.

Date of issue 2022-04-21

SGS Fimko Ltd

Signature


Joonas Leinonen
Certification Manager



Manufacturer

Elko AS
Sandstuveien 68, N-0680, Oslo City, Norway

Manufacturing site

Merten GmbH
Fritz-Kotz-Strasse 8, 51674, Wiehl, North Rhine-Westphalia, Germany

AS M & P Nurst
Ümarmäe 3, Kärddla 92414, Hiiumaa, Estonia

Additional information

The product has certificate P17222303/A3 issued by Intertek Semko AS in accordance with the Nordic Certification Service system.

This certificate replaces previous certificate FI/40514, dated 2019-12-23, due to update of factory information and extension of validity.

L800

Catalogue ID: RS 1091 PT prosjektstikk.
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: H 1091 PT prosjektstikk.
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screwless terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: Plus dbl rehabstikk m j.
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP20 with plus design.

Catalogue ID: RS 1091.
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with screw terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: RS 1091 PT.
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: RS 1091 LAV PT.
Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design.

Additional information

Catalogue ID: 1091 UPT IF.
 Socket-outlet for fixed installation. Standard Sheet III.
 Thermoplastic/Thermosetting, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP44 with splashscreen type L478. For use in cold environment down to -25°C.

Catalogue ID: RS 1091 PT m/lysiode.
 Socket-outlet for fixed installation. With signal light. Standard Sheet III.
 Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design.

L801

Catalogue ID: D 1091 PT.
 Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: Plus 2-vägs snabb m j.
 Socket-outlet for fixed installation.
 Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP20 with Plus design.

Catalogue ID: DR 1091 PT.
 Socket-outlet for fixed installation. Alternative design. Standard Sheet III.
 Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: D 1091 LAV PT.
 Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with RS and Plus design.

L3362

Catalogue ID: RS 1091 PT DELT 440.
 Socket-outlet for fixed installation.
 With split output for separate phases. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design.

Catalogue ID: RS 1091 PT DELT.
 Socket-outlet for fixed installation. With split output. Standard Sheet III.
 Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design.

As shown in the Test Report(s) No(s): 368431, 427913